


# HANCO GENERATING SYSTEMS

## PRIME SERIES



MODEL  
140MSF33DWLP

### POWER RATINGS

140KW STANDBY  
125KW CONTINUOUS  
120/240 VOLT 1 PHASE 60 Hz  
583 AMPS @ 240V 1 PHASE  
3 PHASE RATINGS AVAILABLE  
12 LEAD RECONNECTABLE

### STANDARD SPECIFICATIONS

PERKINS DIESEL ENGINE MODEL 1006-6TA  
HEAVY DUTY RADIATOR  
MECHANICAL GOVERNOR  
VIBRATION ISOLATORS  
HEAVY DUTY 2 STAGE AIR CLEANER  
BATTERY, BATTERY RACK AND CABLES  
12V ELECTRICAL SYSTEM  
INDUSTRIAL GRADE SILENCER  
ALTERNATOR EPOXY COATED  
SOLID STATE VOLTAGE REGULATOR

### HANCO CONTROL PANEL

12V ENGINE GAUGES  
HOUR METER, TEMP GAUGE, OIL PRESSURE  
A/C METERS, AMPS, VOLTS, HERTZ  
HIGH COOLANT TEMP SHUTDOWN  
LOW OIL PRESSURE SHUTDOWN  
CRANK/PRE HEAT START/STOP SWITCH

### OPTIONAL EQUIPMENT

AUTO START CONTROLS  
UL SUBBASE FUEL TANKS  
MAINLINE CIRCUIT BREAKER  
LOW AMP AUTO START FOR SOLAR

# Model

## 140MSF33DWLP / 125MSF22DWLP

### Engine Specifications

Engine Model	Perkins 1006-6TA
Cont. HP @ 1800 RPM	208 HP
Number of Cylinders	6
Aspiration	Turbocharged
Displacement	365.5 cu in (5.99) litre
Bore / Stroke	3.937 (100) / 5.0 (127)
Engine Type	In-Line 6 Cylinder
Forged Steel Dynamically Balanced Crankshaft	
Rotary Injection Pump With Mechanical Gover-	

### Generator Specifications

Model	UCI274H
Rating @ Rise / Ambient	125F / 40 C
Insulation	Class H
Voltage Regulator	SX 460
Winding Leads	12 Lead Reconnectable
Voltage Regulation	Plus / Minus 1.5%

### Fuel Consumption @ Rated Load

50%	4.2 US GAL / HR
75%	6.3 US GAL / HR
100%	8.4 US GAL / HR

### Shipping Characteristics of Basic Unit

Weight - 2851 lbs (no options)  
 Cube - L= 100" W= 34" H= 51" (no options)

### Optional Equipment

2Wire auto start	Low amp start for Solar
Main Line Circuit Breaker	UL Subbase Tank
Electronic Governing	Weather Enclosure
Critical Grade Silencer	Auto Transfer Switch
SS Flex Connector	Sound Enclosure
Battery Trickle Charger	Trailer w/Fuel Cell

Specification subject to change without notice

